

# County Surveyor's Record, Douglas County, Oregon

203

17687

Subdivision of Section 33,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

T 22 S    R 5 W  
C 1/4    S 33

1983

from which

A fir, 6 ins. diam., bears S. 79 1/2° E., 26 lks. dist., mkd. C 1/4 S33 BT.

A fir, 8 ins. diam., bears N. 16 3/4° W., 39 lks. dist., mkd. C 1/4 S33 BT.

From this point, a locally established point, bears N. 66° 12' E., 0.240 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 26 ins. above ground, from which bearing trees mkd. by person(s) unknown.

A fir, 28 ins. diam., bears N. 18° E., 8 1/2 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 24 ins. diam., bears S. 19° E., 50 lks. dist., with healed double blaze.

Descend over broken NE. slope.

53.00      Spur, slopes N. 65° E.; desc. over NW. slope.

68.70      Creek, 21 lks. wide, course NE.; asc. over SE. slope.

76.40      Spur, slopes S. 30° E.; desc. over NE. slope.

79.69      The 1/4 sec. cor. of secs. 28 and 33.

From the 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by Oscar F. Thiel, Deputy County Surveyor, in 1900, and further perpetuated and recorded by Bruce R. Rogers, Deputy County Surveyor, in 1965, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree

A black oak stump, 36 ins. diam., bears S. 43° W., 16 lks. dist., no marks visible.

and a bearing tree recorded by Thiel

A white oak, 20 ins. diam., bears N. 44° E., 78 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Rogers

A fir stump, 21 ins. diam., bears S. 22° W., 41 1/2 lks. dist., with healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 22 S    R 5 W  
          1/4

S 33    |    S 34

1983

F.B. H-222

FD OK  
2-94 M/18-66