

# County Surveyor's Record, Douglas County, Oregon

17689

Subdivision of Section 33,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

(See Haines  
F.B. # 110)

From this point, a locally established point, bears S. 25° 13' E., 0.265 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by person(s) unknown

A sawed fir stump, 28 ins. diam., bears N. 88 1/2° W., 12 lks. dist., with healed blaze.

A sawed fir stump, 30 ins. diam., bears S. 29° E., 22 lks. dist., with scribe marks CW 1/16 S33 BT visible on bark blaze.

Ascend over NE. slope.

63.50 Spur, slopes N. 25° E.; desc. over W. slope.

66.90 Creek, 4 lks. wide, course N. 20° W.; asc. over NE. slope.

73.25 Spur, slopes N. 30° E.; desc. over NW. slope.

80.30 The 1/4 sec. cor. of secs. 32 and 33.

From the center E 1/16 sec. cor. of sec. 33.

N. 0° 04' E., on the N. and S. center line of the NE 1/4 of sec. 33.

Ascend over SE. slope.

0.85 Creek, 2 lks. wide, course N. 85° E.; asc. over SE. slope.

6.15 Spur, slopes N. 80° E.; desc. over NW. slope.

16.70 Creek, 4 lks. wide, course N. 55° E.; asc. over SE. slope.

26.30 Spur, slopes S. 70° E.; desc. over NW. slope.

40.14 The E 1/16 sec. cor. of secs. 28 and 33.

From the point for the W 1/16 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16 S 33

1983

from which

A fir, 15 ins. diam., bears N. 23 1/2° E., 16 1/2 lks. dist., mkd. X BT.

A fir, 15 ins. diam., bears N. 78 1/2° E., 49 lks. dist., mkd. W 1/16 S33 BT.

From this point, a locally established point, bears S. 30° 03' W., 0.249 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 5 ins. above ground, from which bearing trees mkd. by person(s) unknown