

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 33,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

17690

**CHAINS**

A fir, 24 ins. diam., bears N. 14 1/2° E., 33 lks. dist., with healed double blaze.

A fir, 13 ins. diam., bears N. 57° W., 71 lks. dist., with healed double blaze.

From this same point, the standard cor. of secs. 4 and 5, T. 23 S., R. 5 W., bears N. 89° 54' W., 14.94 chs. dist., described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 23 S., R. 5 W. (Fifth Standard Parallel South), executed concurrently under this same Group.

N. 0° 04' E., on the N. and S. center line of the SW 1/4 of sec. 33.

Ascend over SW. slope, through heavy timber and dense undergrowth.

9.50 Spur, slopes S. 35° E.; asc. over SE. slope.

19.30 Top of ascent, slopes E.; desc. over NE. slope.

19.81 Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the SW 1/4.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 33

1983

from which

A fir, 8 ins. diam., bears S. 12 1/2° E., 50 lks. dist., mkd. SW 1/16 S33 BT.

A fir, 6 ins. diam., bears N. 32 3/4° W., 12 1/2 lks. dist., mkd. X BT.

From this point, a locally established point, bears S. 81° 21' W., 0.506 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 5 ins. above ground, from which a bearing tree mkd. by person(s) unknown.

A fir, 15 ins. diam., bears N. 74 1/4° W., 40 lks. dist., with healed double blaze.

Descend over NE. slope.

21.85 Ravine, drains SE.; asc. over SW. slope.

27.70 Ridge, bears N. 80° W. and S. 80° E.; desc. over broken NE. slope.

28.15 Gravelled road, 25 lks. wide, bears N. 80° E.; desc. over broken NE. slope.

39.63 The center W 1/16 sec. cor. of sec. 33.

From the center S 1/16 sec. cor. of sec. 33.

S. 89° 50' W., on the E. and W. center line of the SW 1/4 of sec. 33.