

County Surveyor's Record, Douglas County, Oregon

17694

T. 18 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The geographic position of the corner of sections 25 and 36 only, on the east boundary of the township, as scaled from the United States Geological Survey quadrangle map, "ROMAN NOSE MTN., OREGON", published in 1942, is as follows:

Latitude 43° 52.6' N. Longitude 123° 34.7' W.

The mean magnetic declination is 19° 27' E.

Dependent Resurvey of a Portion of the South Boundary
(Fourth Standard Parallel South),
T. 18 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon, U.S. Deputy Surveyor, in 1855, the survey by Laban H. Wheeler, U.S. Deputy Surveyor, in 1881, the survey by Charles M. Collier, U.S. Deputy Surveyor, in 1891, and the resurvey by Guy H. Richardson, Cadastral Engineer, and Norman D. Price, Transitman, in 1927-28)

Beginning at the standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 18 S R 8 W
 S C
 S 35 | S 36

1927

from which the remains of the original bearing trees

A fir, 63 ins. diam., bears N. 81° E., 86 lks. dist., with healed blaze. (Record, 83 lks.)

A root hole, bears N. 9° W., 32 lks. dist., with a down fir, 53 ins. diam., alongside, with healed blaze.

and a bearing tree mkd. by person(s) unknown

A hemlock, 18 ins. diam., bears N. 45 1/2° E., 21 lks. dist., with healed blaze.

and a new bearing tree

A fir, 42 ins. diam., bears N. 73° W., 81 lks. dist., mkd. T18S R8W S35 SC BT.

Set a 6 ft. steel fence post alongside the iron post.

S. 89° 57' W., on the S. bdy. of sec. 35, marking and blazing the true line.

Descend 185 ft. over NW. slope, through heavy timber and medium undergrowth.

8.00 Head of ravine, drains N. 25° W.; asc. 45 ft. over NE. slope.

12.80 Spur, slopes W., from S. 75° E.; desc. 90 ft. along top of spur.

20.165 Point for the standard E 1/16 sec. cor. of sec. 35.