

County Surveyor's Record, Douglas County, Oregon

17695

Dependent Resurvey, Portion of S. Bdy.
(Fourth Standard Parallel South),
T. 18 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 18 S R 8 W
E 1/16 S 35
1980

from which

A fir, 39 ins. diam., bears N. 26 1/2° E., 31 1/2 lks. dist., mkd. E 1/16 S35 SC BT.

A fir, 6 ins. diam., bears N. 56 1/2° W., 37 lks. dist., mkd. E 1/16 S35 SC BT.

Set a 6 ft. steel fence post alongside the iron post.

Corner is located on spur, slopes N. 75° W. from E. Descend 100 ft. over SW. slope.

26.45

The closing cor. of secs. 2 and 3, T. 19 S., R. 8 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 18 S R 8 W
S 35
S 3 | S 2
T 19 S C C R 8 W
1927

from which the remains of the original bearing trees

A fir, size indeterminate, bears N. 47 3/4° E., 32 lks. dist., no marks visible.
(Record, 35 lks.)

A sawed fir stump, 48 ins. diam., bears S. 35° E., 87 lks. dist., with rotted blaze, no marks visible.

A fir snag, 21 ins. diam., bears S. 45° W., 33 lks. dist., with rotted blaze, no marks visible. (Record, 38 lks.)

and new bearing trees

A fir, 7 ins. diam., bears S. 33 1/4° E., 67 1/2 lks. dist., mkd. T19S R8W S2 CC BT.

A fir, 17 ins. diam., bears S. 75 1/2° W., 63 1/2 lks. dist., mkd. T19S R8W S3 CC BT.

Descend 65 ft. over SW. slope.

28.30

The original standard 1/4 sec. cor. of sec. 2, T. 19 S., R. 8 W., changed to an angle point, by Richardson and Price in 1927-28, monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

A P
T 19 S R 8 W
S 3
1927

from which the remains of an original bearing tree