

County Surveyor's Record, Douglas County, Oregon

17697

Dependent Resurvey, Portion of S. Bdy.
(Fourth Standard Parallel South),
T. 18 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

28.70

The original standard cor. of secs. 2 and 3, T. 19 S., R. 8 W., changed to an angle point by Richardson and Price in 1927-28, monumented with an iron post, 1 in. diam., firmly set, the top 4 ins. below the surface of the ground, with brass cap mkd.

T 19 S R 8 W
S 3
A P
1928

from which the remains of bearing trees mkd. by Richardson and Price

A fir snag, 15 ins. diam., bears S. 35 1/2° E., 36 lks. dist., with scribe marks AP T19 R8 visible on partially healed blaze.

A fir, 42 ins. diam., bears S. 44 3/4° W., 18 lks. dist., with healed blaze.

and a new bearing tree

A fir, 15 ins. diam., bears S. 75 3/4° E., 44 1/2 lks. dist., mkd. AP S3 BT.

Set a 6 ft. steel fence post alongside the iron post.

N. 89° 28' W., beginning new measurement.

Ascend 15 ft. over nearly level bottom land.

1.70

Siuslaw Access Road, paved, 35 lks. wide, bears N. 85° E. and S. 85° W.

11.72

The standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 18 S R 8 W
S C
S 34 | S 35
1927

from which the original bearing trees

A hollow triple maple, 28 ins. diam., bears N. 18° E., 100 lks. dist., with healed blaze. (Record, N. 28 1/4° E., 106 lks.)

A maple, 33 ins. diam., bears N. 11° W., 102 lks. dist., with scribe marks 8W S3 visible on partially healed blaze. (Record, 108 lks.)

Set a 6 ft. steel fence post alongside the iron post.

Land, mountainous and rolling river bottom.

Soil, rocky clay and sandy loam.

Timber, fir, hemlock, maple, alder, and chinquapin; undergrowth, vine maple, hazel, salal, Oregon grape, huckleberry, blackberry, arrowwood, and fern.

N. 89° 45' W., on the S. bdy. of sec. 34.

Ascend 20 ft. along S. slope, through heavy timber and dense undergrowth.