

# County Surveyor's Record, Douglas County, Oregon

17699

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which bearing trees mkd. by Price and Tillman</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 50° W., 52 lks. dist., with healed blaze. (Record, S. 53 1/2° W., 50 lks.)</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 43 1/2° W., 44 lks. dist., with healed blaze. (Record, N. 39 1/4° W., 42 lks.)</p> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <p>N. 89° 22' W., bet. secs. 25 and 36, marking and blazing the true line.</p> <p>Descend 670 ft. over SW. slope, through moderate timber and undergrowth.</p>
18.70	Haskins Creek, dry, 12 lks. wide, course N. 20° E.; asc. 305 ft. over steep NE. slope.
25.70	Spur, slopes N.; desc. 300 ft. over NW. slope.
31.60	Dry creek bed, 5 lks. wide, course N. 5° W.; asc. 60 ft. over SE. slope.
34.20	Spur, slopes N. 40° E.; desc. 60 ft. over SW. slope.
39.40	Dry creek bed, 3 lks. wide, course N. 60° E.; asc. 5 ft. over NE. slope.
39.63	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S    R 8 W</p> <p>1/4    <u>S 25</u></p> <p>          S 36</p> <p>          1980</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 75 ins. diam., bears N. 75 1/4° E., 122 lks. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears S. 66° E., 128 lks. dist., mkd. 1/4 S36 BT.</p> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <p>Ascend 110 ft. over NE. slope.</p>
43.70	Top of ascent, slopes N.; desc. 20 ft. over NW. slope.
46.10	Ravine, drains N. 70° E.; asc. 475 ft. over steep SE. slope.
56.80	Ridge, bears N. 20° E. and S.; desc. 570 ft. over SW. slope.
57.00	Dirt road, 15 lks. wide, bears N. 15° E. and S. 10° W.
79.26	The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, under protruding SE. lip of boulder, 15 x 12 x 8 ft. above ground, no marks remaining, with brass cap mkd.