

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17700**
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 19 S	R 8 W
S 26	S 25
S 35	S 36
1952	

from which the remains of bearing trees mkd. by Lytle and Norseth

A fir, 33 ins. diam., bears N. 49° E., 19 lks. dist., with healed blaze.

A root hole, bears S. 44° E., 29 lks. dist., with a down fir, 24 ins. diam., alongside, with healed blaze.

A root hole, bears S. 47° W., 74 lks. dist., with a down fir, 20 ins. diam., alongside, with healed blaze. (Record, S. 21 1/2° W., 21 lks.)

A fir snag, 21 ins. diam., bears N. 21 1/2° W., 21 lks. dist., with healed blaze. (Record, N. 47° W., 74 lks.)

and new bearing trees

A fir, 30 ins. diam., bears S. 64° E., 50 lks. dist., mkd. T19S R8W S36 BT.

A cedar, 16 ins. diam., bears S. 26° W., 96 lks. dist., mkd. T19S R8W S35 BT.

A fir, 25 ins. diam., bears N. 41 1/2° W., 42 lks. dist., mkd. T19S R8W S26 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, dogwood, cherry, chinquapin, yew, and madrone; undergrowth, vine maple, arrowwood, hazel, salmonberry, huckleberry, Oregon grape, salal, poison oak, and fern.

N. 0° 06' E., bet. secs. 25 and 26.

Ascend 590 ft. over SW. slope, through scattering timber and moderate undergrowth.

40.22

Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S	R 8 W
1/4	
S 26	S 25
1980	

from which

A fir, 14 ins. diam., bears N. 13° E., 27 lks. dist., mkd. 1/4 S25 BT.