

# County Surveyor's Record, Douglas County, Oregon

17701

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- A fir, 24 ins. diam., bears N. 78 3/4° W.,  
39 1/2 lks. dist., mkd. 1/4 S26 BT.
- Set a 6 ft. steel fence post alongside the iron post.
- Ascend 20 ft. over SW. slope.
- 41.50 Ridge, bears N. 60° W. and S. 60° E., also dirt road,  
12 lks. wide, bears N. 50° W. and S. 50° E.; desc.  
300 ft. over steep NE. slope.
- 47.70 Ravine, drains N. 70° E.; asc. 80 ft. over SE. slope.
- 50.70 Spur, slopes E.; desc. 120 ft. over N. slope.
- 53.70 Ravine, drains N. 70° E.; asc. 30 ft. along E. slope.
- 59.40 Spur, slopes N. 60° E.; desc. 155 ft. over steep NE.  
slope.
- 64.80 Dry creek bed, 3 lks. wide, course N. 70° E.; asc.  
180 ft. over SE. slope.
- 69.30 Spur, slopes E.; desc. 70 ft. over N. slope.
- 71.00 Ravine, drains S. 80° E.; asc. 300 ft. over S. slope.
- 76.90 Ridge, bears N. 35° E. and S. 25° W.; desc. 110 ft. over  
NE. slope.
- 80.44 The cor. of secs. 23, 24, 25, and 26, monumented with an  
iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd.

T 19 S	R 8 W
S 23	S 24
S 26	S 25

1958

from which the remains of the original bearing trees

A burned cedar snag, 11 ins. diam., bears  
N. 12 1/2° E., 45 lks. dist., no marks visible.  
(Record, 41 lks.)

A rotted fir stump, size indeterminate, bears  
S. 77° E., 127 lks. dist., no marks visible.

A fir snag, 33 ins. diam., bears S. 14 3/4° W.,  
112 lks. dist., with scribe marks R8W visible  
on opened blaze. (Record, 105 lks.)

A fir snag, 46 ins. diam., bears N. 61 1/2° W.,  
68 lks. dist., with scribe marks T19S R8W visible  
on burned blaze.

and bearing trees mkd. by Brooks

A fir, 25 ins. diam., bears N. 15 1/2° E., 95 lks.  
dist., with healed blaze. (Record, N. 17° E.,  
66 lks.)

A fir, 12 ins. diam., bears S. 40° E., 23 lks.  
dist., with healed blaze.

A fir, 23 ins. diam., bears S. 37° W., 14 lks.  
dist., with healed blaze.