

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17702
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 13 ins. diam., bears N. 22 1/2° W., 88 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, dogwood, and maple; undergrowth, vine maple, hazel, arrowwood, salmonberry, huckleberry, salal, Oregon grape, poison oak, and fern.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 19 S	R 19 S
S 24	S 7 W
S 25	S 30
R 8 W	
1949	

from which bearing trees mkd. by Price and Tillman

A fir, 13 ins. diam., bears S. 4° W., 90 lks. dist., with healed blaze.

A madrone, 10 ins. diam., bears N. 26° W., 22 lks. dist., with scribe marks 19S 48W S visible on partially healed blaze.

N. 89° 55' W., bet. secs. 24 and 25.

Descend 370 ft. over rolling S. slope, through moderate timber and undergrowth.

15.25 Creek, 2 lks. wide, course S. 30° W.; asc. 180 ft. over steep SE. slope.

19.935 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S 24
	S 25
1980	

from which

A fir, 13 ins. diam., bears N. 69 1/2° E., 37 lks. dist., mkd. E 1/16 S24 BT.

A fir, 20 ins. diam., bears S. 5 1/2° E., 20 1/2 lks. dist., mkd. E 1/16 S25 BT.

Set a 6 ft. steel fence post alongside the iron post.

Ascend slightly over SE. slope.

20.20 Spur, slopes S. 20° E.; desc. 30 ft. over SW. slope.

21.40 Top of rock bluff, bears N. and S.; desc. 140 ft. over steep W. slope.

23.50 Base of rock bluff; desc. 180 ft. over SW. slope.

36.50 Creek, 2 lks. wide, course S. 20° W.; asc. 65 ft. over SE. slope.