

County Surveyor's Record, Douglas County, Oregon

17703 Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
37.90	Spur, slopes S.; desc. 40 ft. over SW. slope.
39.87	<p>The 1/4 sec. cor. of secs. 24 and 25, reestablished at proportionate distance and recorded by William A. Eimstad, Registered Land Surveyor, No. 377, in 1979 and is accepted as the best available evidence of the position of the original corner, monumented with an iron bar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Eimstad</p> <p style="padding-left: 40px;">An alder, 20 ins. diam., bears N. 47° E., 17 lks. dist., with scribe marks 1/4 S24 BT visible on open blaze.</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears S. 8° E., 22 1/2 lks. dist., with scribe marks 1/4 S25 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron bar, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 19 S R 8 W</p> <p> 1/4 <u>S 24</u></p> <p> S 25</p> <p> 1980</p> </div> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 55' W., beginning new measurement.</p> <p>Descend 20 ft. over creek bottom.</p>
1.50	Haskins Creek, 10 lks. wide, course N. 40° W., from S. 20° E.; asc. 340 ft. over NE. slope.
10.70	Spur, slopes N. 5° E.; desc. 320 ft. over NW. slope.
17.35	Creek, 4 lks. wide, course N. 10° E.; asc. 115 ft. over SE. slope.
19.94	<p>A corner, established and recorded by William A. Eimstad, Registered Land Surveyor, No. 377, in 1979, monumented with an iron bar, 5/8 in. diam., firmly set, flush with ground, from which bearing trees mkd. by Eimstad</p> <p style="padding-left: 40px;">A maple, 12 ins. diam., bears S. 6° E., 90 1/2 lks. dist., with scribe marks W 1/16 S25 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 19 1/4° W., 84 lks. dist., with scribe marks W 1/16 S24 BT visible on open blaze.</p> <p>Ascend 415 ft. over S. slope.</p>
28.05	Spur, slopes S. 20° E.; asc. 55 ft. along S. slope.
32.15	Ridge, bears N. 55° E. and S. 50° W.; desc. 110 ft. over NW. slope.
35.15	Ravine, drains N. 35° W.; asc. 70 ft. over NE. slope.
39.87	The cor. of secs. 23, 24, 25, and 26.