

# County Surveyor's Record, Douglas County, Oregon

17705

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A sawed hemlock stump, 31 ins. diam., bears  
S. 5° W., 10 lks. dist., with nail and tag.


A sawed fir stump, 32 ins. diam., bears  
N. 66 1/2° W., 59 lks. dist., with nail and tag.

and a bearing tree mkd. by person(s) unknown

A hemlock, 20 ins. diam., bears S. 40 1/4° W.,  
72 lks. dist., with scribe marks /// RT visible  
on open blaze and a nail at the base.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in  
the ground, directly over the iron bar, with brass cap  
mkd.



from which new bearing trees

A hemlock, 16 ins. diam., bears S. 6 1/2° E.,  
126 lks. dist., mkd. 1/4 S13 BT.

A fir, 22 ins. diam., bears S. 65 1/2° W.,  
111 lks. dist., mkd. 1/4 S14 BT.

Set a 6 ft. steel fence post alongside the iron post.

N. 0° 48' E., beginning new measurement.

Descend 30 ft. over bottom land.

7.10 Left bank of Siuslaw River, bears S. 75° W. and  
N. 75° E., course S. 75° W.; thence across river.

8.70 Right bank of Siuslaw River, bears S. 75° W. and  
N. 75° E.; asc. 330 ft. over SE. slope.

9.10 Siuslaw Access Road, paved, 25 lks. wide, bears N. 80° E.  
and S. 75° W.

20.02 The N 1/16 sec. cor. of secs. 13 and 14, established by  
person(s) unknown, and is accepted as the corner,  
monumented with an iron bar, 5/8 in. diam., firmly set,  
protruding 2 ins. above ground, from which locally mkd.  
bearing trees

A fir, 6 ins. diam., bears N. 81 3/4° W., 11 lks.  
dist., with scribe marks N 1/16 S14 BT visible  
on open blaze.

A maple, 12 ins. diam., bears N. 10 1/2° W., 7 lks.  
dist., with scribe marks /// RT visible on open  
blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in  
the ground, directly over the iron bar, with brass cap mkd.