

County Surveyor's Record, Douglas County, Oregon

17707

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. 44° W.,
85 lks. dist., mkd. T19S R8W S14 BT.

A hemlock, 8 ins. diam., bears N. 15° W.,
46 1/2 lks. dist., mkd. T19S R8W S11 BT.

Set a 6 ft. steel fence post alongside the iron post.

Land, mountainous and rolling.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, dogwood, and alder;
undergrowth, vine maple, hazel, arrowwood, blackberry,
thimbleberry, salal, Oregon grape, and fern.

From the cor. of secs. 26, 27, 34, and 35, perpetuated by
person(s) unknown, monumented with an iron bar, 5/8 in.
diam., firmly set, the top 4 ins. below surface of
ground, from which the remains of bearing trees mkd. by
Lytle and Norseth

A sawed fir stump, 70 ins. diam., bears
S. 5 1/2° E., 366 lks. dist., with scribe marks
T19S R8 visible on partially healed blaze.
(Record, S. 6 1/4° E., 362 lks.)

A root hole, bears S. 23 1/4° W., 211 lks. dist.,
with a down alder, 19 ins. diam., alongside
with healed blaze.

A maple, 28 ins. diam., bears N. 71 1/4° W., 86 lks.
dist., with healed blaze. (Record, N. 70° W.)

~~At the corner point~~

~~Set an iron post, 28 ins. diam., bears N. 71 1/4° W., 86 lks.
dist., with healed blaze. (Record, N. 70° W.)~~

At the corner point

Set an iron post, 28 ins. long, 2 1/2-ins. diam., 24 ins. in
the ground, to solid rock, directly over the iron bar, in
concrete, with brass cap mkd.

T 19 S	R 8 W
S 27	S 26
S 34	S 35
1980	

from which new bearing trees

An alder, 8 ins. diam., bears N. 70 1/2° E., 34 lks.
dist., mkd. T19S R8W S26 BT on bark.

An alder, 11 ins. diam., bears S. 7° E., 192 lks.
dist., mkd. T19S R8W S35 BT on bark.

An alder, 10 ins. diam., bears S. 24° W., 57 lks.
dist., mkd. T19S R8W S34 BT on bark.

Set a 6 ft. steel fence post alongside the iron post.

From this point, Esmond Creek, 20 lks. wide, bears South,
20 lks. dist., course W.

N. 0° 03' E., bet. secs. 26 and 27.

Ascend 610 ft. over SE. slope, through medium timber and
dense undergrowth.

Esmond Creek Road, paved, 25 lks. wide, bears N. 45° E.,
and W., in curve.