

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines 17708
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS											
28.10	Spur ridge, bears N. 35° W. and S., curving SW.; desc. 40 ft. over NE. slope.										
30.60	Head of ravine, drains N. 85° E.; asc. 130 ft. over SE. slope.										
37.00	Spur ridge, bears N. 45° E. and S. 5° W.; desc. 35 ft. over NW. slope.										
39.30	Head of ravine, drains N. 85° W.; asc. 10 ft. over SW. slope.										
40.63	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 19 S</td> <td style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td></td> <td style="text-align: center;">1/4</td> </tr> <tr> <td style="padding: 0 10px;">S 27</td> <td style="text-align: center;"> </td> <td style="padding: 0 10px;">S 26</td> </tr> <tr> <td></td> <td style="text-align: center;">1980</td> <td></td> </tr> </table>	T 19 S	R 8 W		1/4	S 27		S 26		1980	
T 19 S	R 8 W										
	1/4										
S 27		S 26									
	1980										
	from which										
	A fir, 16 ins. diam., bears S. 58° E., 15 lks. dist., mkd. 1/4 S26 BT.										
	A fir, 25 ins. diam., bears S. 35 1/4° W., 23 lks. dist., mkd. 1/4 S27 BT.										
	Set a 6 ft. steel fence post alongside the iron post.										
	Ascend 80 ft. over SW. slope.										
44.50	Spur, slopes N. 80° W.; desc. 50 ft. over NW. slope.										
46.40	Creek, 2 lks. wide, course N. 80° W.; asc. 135 ft. over SW. slope.										
56.00	Dirt road, 10 lks. wide, on ridge, bears S. 40° E. and N. 75° W.; desc. 125 ft. over NE. slope.										
59.10	Ravine, drains N. 60° E.; asc. 40 ft. over SE. slope.										
61.60	Spur, slopes N. 60° E.; desc. 105 ft. over NE. slope.										
64.70	Ravine, drains N. 80° E.; asc. 75 ft. over SE. slope.										
67.90	Ridge, bears N. 30° E.; and S. 20° W.; desc. 180 ft. over NW. slope.										
69.60	Gravelled road, 25 lks. wide, bears N. 20° E. and S. 60° W., in curve.										
81.26	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, the top 12 ins. below surface of road fill, with brass cap mkd.										
	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 19 S</td> <td style="padding: 0 10px;">R 8 W</td> </tr> <tr> <td style="padding: 0 10px;">S 22</td> <td style="padding: 0 10px;">S 23</td> </tr> <tr> <td style="padding: 0 10px;">S 27</td> <td style="padding: 0 10px;">S 26</td> </tr> <tr> <td></td> <td style="text-align: center;">1958</td> </tr> </table>	T 19 S	R 8 W	S 22	S 23	S 27	S 26		1958		
T 19 S	R 8 W										
S 22	S 23										
S 27	S 26										
	1958										
	from which the remains of an original bearing tree										