

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17710**
 T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 12 ins. diam., bears S. 11° W., 31 lks.
 dist., mkd. 1/4 S26 BT.

A fir, 15 ins. diam., bears N. 20 1/2° W., 19 lks.
 dist., mkd. 1/4 S23 BT.

Set a 6 ft. steel fence post alongside the iron post.

Land, mountainous.

Soil, rotky clay.

Timber, fir, hemlock, cedar, alder, dogwood, and maple;
 undergrowth, vine maple, arrowwood, hazel, huckleberry,
 salal, Oregon grape, and fern.

From the cor. of secs. 2, 3, 10, and 11, perpetuated and
 recorded by William A. Eimstad, Registered Land Surveyor,
 No. 377, in 1978, monumented with an iron bar, 5/8 in.
 diam., firmly set, projecting 4 ins. above ground, from
 which the remains of the original bearing trees

A broken fir stump, 15 ins. diam., bears
 N. 7 1/2° E., 13 lks. dist., with scribe marks
 W BT visible on open and rotted blaze.
 (Record, N. 24 1/4° E.)

A fir, 23 ins. diam., bears S. 6° E., 25 lks.
 dist., with healed blaze. (Record, S. 17 1/2° E.)

A fir, 29 ins. diam., bears S. 14 1/2° W., 38 lks.
 dist., with healed blaze. (Record, S. 6° W.,
 33 lks.)

A fir, 18 ins. diam., bears N. 32 1/2° W., 21 lks.
 dist., with illegible scribe marks visible on
 partially opened blaze. (Record, N. 17 1/2° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
 the ground, directly over the iron bar, with brass cap
 mkd.

T 19 S	R 8 W
S 3	S 2
S 10	S 11
1980	

No other suitable trees available within limits.

Set a 6 ft. steel fence post alongside the iron post.

N. 88° 34' W., bet. secs. 3 and 10.

Descend 70 ft. along S. slope, through medium timber and
 moderate undergrowth.

6.20 Spur, slopes S.; desc. 250 ft. over steep W. slope.

13.90 Cedar Creek, 6 lks. wide, course S. 30° W.; asc. 170 ft.
 over steep SE. slope.

19.93 Point for the E 1/16 sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
 the ground, with brass cap mkd.

E 1/16	S 3
	S 10
1980	