

County Surveyor's Record, Douglas County, Oregon

17711 Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 66 1/2° W., 18 1/2 lks. dist., mkd. E 1/16 S10 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 36 1/2° W., 19 lks. dist., mkd. E 1/16 S3 BT.</p> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <p>Ascend 30 ft. over SE. slope.</p>
20.30	Spur, slopes S.; desc. 140 ft. over SW. slope.
29.90	Creek, 2 lks. wide, course S. 10° W.; asc. 65 ft. over SE. slope.
33.30	Spur, slopes S. 20° E.; desc. 70 ft. over SW. slope.
37.80	Creek, 2 lks. wide, course S. 20° W.; asc. 30 ft. over SE. slope.
39.00	Spur, slopes S. 10° W.; desc. 14 ft. over SW. slope.
39.86	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner, located in Siuslaw Access Road, paved, 30 lks. wide, bears N. 55° W. and S. 55° E.</p> <p>Set a railroad spike, 1/2 in. square, 6 ins. long, flush with pavement, with top mkd.</p> <p style="text-align: center;">1/4 X</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 65° E., 66 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 22° E., 108 1/2 lks. dist., mkd. 1/4 S10 BT.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 35 lks. dist., mkd. T19S R8W 1/4 S10 RM 1980 and an arrow pointing to the corner.</p> <p>Set a 6 ft. steel fence post alongside the reference monument.</p> <p>Descend 40 ft. over SW. slope.</p>
65.00	Bottom of descent slopes S.; asc. 90 ft. over SE. slope.
68.00	Enter logged area, edge bears N. and S.
71.30	Paved road, 30 lks. wide, bears S. 85° W. and N. 75° E., in curve, also spur, slopes S. 85° W.; desc. 40 ft. over NW. slope.
79.72	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., projecting 4 ins. above ground, with brass cap mkd.

T 19 S		R 8 W
S 4		S 3
S 9		S 10

1952