

County Surveyor's Record, Douglas County, Oregon

17713


Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A twin maple, 50 ins. diam., bears N. 33 1/4° W., 101 lks. dist., with rotted out blaze, no marks visible. (Record, N. 28° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which new bearing trees

A fir, 18 ins. diam., bears S. 71 1/4° E., 129 lks. dist., mkd. 1/4 S3 BT.


An alder, 13 ins. diam., bears N. 18 1/2° W., 7 lks. dist., mkd. 1/4 S4 BT on bark.

Set a 6 ft. steel fence post alongside the iron post.

North, beginning new measurement.

Descend 20 ft. over river bottom.

- 4.10 Right bank of Siuslaw River, bears N. 35° E. and S. 35° W., course N. 35° E.; thence across river.
 - 9.80 Left bank of Siuslaw River, bears same; asc. 70 ft. over SE. slope.
 - 13.20 Spur, slopes NE.; desc. 60 ft. over NE. slope.
 - 15.35 Creek, 6 lks. wide, course S. 55° E.; asc. 50 ft. over S. slope.
 - 20.01 Point for the N 1/16 sec. cor. of secs. 3 and 4.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A fir, 8 ins. diam., bears S. 69° E., 16 lks. dist., mkd. N 1/16 S3 BT.

A fir, 15 ins. diam., bears N. 88° W., 26 lks. dist., mkd. N 1/16 S4 BT.

Set a 6 ft. steel fence post alongside the iron post.

Ascend 350 ft. over S. slope.

- 22.45 Abandoned gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.