

# County Surveyor's Record, Douglas County, Oregon

17714

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

- 36.40 Abandoned road, 20 lks. wide, bears N. 30° W. and S. 30° E.
- 42.50 Spur ridge, bears N. 60° W. and S. 60° E.; desc. 420 ft. over steep N. slope.
- 51.10 Left bank of Siuslaw River, bears N. 85° W. and S. 85° E., course N. 85° W.; thence across river.
- 52.60 Right bank of Siuslaw River, bears same; asc. 60 ft. over bottom land.
- 58.50 Siuslaw Access Road, paved, 30 lks. wide, bears E. and W.
- 61.80 The original closing cor. of secs. 3 and 4, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 18 S	R 8 W
S 34	
S 4	S 3
T 19 S	R 8 W
C C	
1927	

from which the remains of an original bearing tree

A rotted fir stump, size indeterminate, bears S. 68° W., 4 lks. dist., with scribe marks BT visible in reverse and relief on overgrowth. (Record, S. 22° W., 8 lks.)

and bearing trees mkd. by Richardson and Price

A rotted sawed fir stump, 32 ins. diam., bears N. 84 3/4° E., 60 lks. dist., with scribe marks T19S 8W S visible on open and rotted blaze. (Record, S. 89° 3/4° E.)

A rotted sawed fir stump, 30 ins. diam., bears S. 18° W., 18 lks. dist., with fragmentary scribe marks visible on open and rotted blaze. (Record, S. 12 1/2° W., 24 lks.)

Remove allmarks from brass cap and add marks AM 1980.

- 61.88 Intersect the S. bdy. (Fourth Standard Parallel South) of sec. 34, T. 18 S., R. 8 W.
- True point for the closing cor. of secs. 3 and 4.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 18 S	R 8 W
S 34	
S 4	S 3
T 19 S	R 8 W
C C	
1980	

from which

A fir, 11 ins. diam., bears S. 65° E., 25 lks. dist., mkd. T19S R8W S3 CC BT.

A fir, 11 ins. diam., bears S. 3 1/4° W., 53 lks. dist., mkd. T19S R8W S4 CC BT.

Set a 6 ft. steel fence post alongside the iron post.