

County Surveyor's Record, Douglas County, Oregon

17717

Remonumentation of Certain Original Corner Points,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 40 ins. diam., bears N. 55° E., 25 lks. dist., with healed blaze.

A root hole, bears S. 22° E., 36 lks. dist., with a down fir alongside, 12 ins. diam., with scribe marks 1/4 S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S R 8 W
1/4 $\frac{S 12}{S 13}$
1980

from which a new bearing tree

A fir, 30 ins. diam., bears S. 15° W., 54 1/2 lks. dist., mkd. 1/4 S13 BT.

Set a 6 ft. steel fence post alongside the iron post.

The cor. of secs. 1, 2, 11, and 12, perpetuated by person(s) unknown, monumented with an iron bar, 3/4 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees

A maple clump, bears N. 56° E., 52 lks. dist.

A sawed fir stump, 62 ins. diam., bears S. 82 1/4° E., 40 lks. dist., with scribe mark B visible on opened blaze.

and locally mkd. bearing trees

A fir, 10 ins. diam., bears N. 15° E., 61 1/2 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 86° E., 24 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears S. 19 1/2° W., 10 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron bar, with brass cap mkd.

T 19 S R 8 W
S 2 | S 1
S 11 | S 12
1980

from which new bearing trees

An alder, 11 ins. diam., bears S. 17° E., 80 1/2 lks. dist., mkd. T19S R8W S12 BT on bark.

An alder, 13 ins. diam., bears N. 35 1/2° W., 33 lks. dist., mkd. T19S R8W S2 BT on bark.

Set a 6 ft. steel fence post alongside the iron post.