

County Surveyor's Record, Douglas County, Oregon

17719

Remonumentation of Certain Original Corner Points,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The 1/4 sec. cor. of secs. 10 and 11, monumented with the remains of the original corner tree, a fir snag, 45 ins. diam., with healed blaze on W. side, from which the remains of the original bearing trees

A fir snag, 38 ins. diam., bears N. 65° E.,
35 lks. dist., with scribe marks 4 T visible
on opened blaze.

A fir snag, 48 ins. diam., bears N. 71 1/4° W.,
92 lks. dist., with healed blaze.

and new bearing trees and reference monument

A fir, 8 ins. diam., bears N. 81° E., 14 lks.
dist., mkd. 1/4 S11 BT.

A fir, 11 ins. diam., bears S. 11° W., 26 lks.
dist., mkd. 1/4 S10 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam., set
24 ins. in the ground, for a reference monument,
bears S. 30° W., 20 lks. dist., with brass cap
mkd. T19S R8W 1/4 S10 RM 20LS 1980 and an arrow
pointing to the corner.

Set a steel fence post alongside the reference monument.

The 1/4 sec. cor. of secs. 2 and 3, determined from the original bearing trees

A fir, 25 ins. diam., bears S. 74 1/2° E., 21 lks.
dist., with scribe marks 1/ visible on opened
blaze.

A fir, 35 ins. diam., bears N. 25° W., 20 lks.
dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 19 S R 8 W
 1/4
 |
S 3 | S 2
 |
 1980

Set a 6 ft. steel fence post alongside the iron post.

The corner is located 60 lks. North of dirt road, 20 lks.
wide, bears E. and W.

The 1/4 sec. cor. of secs. 22 and 27, determined from the remains of the original bearing trees

A fir, 50 ins. diam., bears N. 26° E., 29 lks.
dist., with healed blaze.

A sawed fir stump, 43 ins. diam., bears
S. 39 1/2° W., 19 lks. dist., with scribe marks
1/4 S visible on opened and rotted blaze.