

# County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 19 S., R. 8 W., Willamette Meridian, Oregon

17720

**CHAINS**

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S    R 8 W  
1/4  $\frac{S 22}{S 27}$   
1980

from which a new bearing tree

A maple, 15 ins. diam., bears S. 8° E., 114 1/2 lks. dist., mkd. 1/4 S27 BT.

Set a 6 ft. steel fence post alongside the iron post.

The 1/4 sec. cor. of secs. 15 and 22, determined from the remains of the original bearing trees

A sawed fir stump, 50 ins. diam., bears N. 50° E., 16 lks. dist., with scribe marks 4 S visible on opened blaze. (Record, 13 lks.)

A fir, 58 ins. diam., bears S. 75° W., 30 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 19 S    R 8 W  
1/4  $\frac{S 15}{S 22}$   
1980

from which a new bearing tree

A fir, 18 ins. diam., bears N. 25 1/2° E., 17 lks. dist., mkd. 1/4 S15 BT.

Set a 6 ft. steel fence post alongside the iron post.

The corner is located 30 lks. North of gravelled road, 25 lks. wide, bears E. and W.

The 1/4 sec. cor. of secs. 10 and 15, determined from the remains of an original bearing tree

A sawed fir stump, 25 ins. diam., bears S. 7° W., 17 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S    R 8 W  
1/4  $\frac{S 10}{S 15}$   
1980

from which new bearing trees