

County Surveyor's Record, Douglas County, Oregon

17721

Remonumentation of Certain Original Corner Points,
T. 19 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A chinquapin, 11 ins. diam., bears S. 53° W.,
34 1/2 lks. dist., mkd. 1/4 S15 BT on bark.

A fir, 6 ins. diam., bears N. 81 1/2° W.,
5 1/2 lks. dist., mkd. 1/4 S10 BT.

Set a 6 ft. steel fence post alongside the iron post.


The 1/4 sec. cor. of secs. 29 and 30, determined from the
remains of the original bearing trees

A fir, 55 ins. diam., bears N. 64 3/4° E.,
41 lks. dist., with scribe mark S visible
on opened blaze.

A root hole, bears N. 77° W., 19 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in
the ground, to solid rock, in a mound of stone, 2 ft.
base, to top, with brass cap mkd.



from which a new bearing tree

A fir, 6 ins. diam., bears S. 52 1/4° W., 33 lks.
dist., mkd. 1/4 S30 BT.

Set a 6 ft. steel fence post alongside the iron post.


The 1/4 sec. cor. of secs. 18 and 19, determined from the
original bearing trees

A fir, 64 ins. diam., bears S. 77° E., 32 lks.
dist., with healed blaze.

A fir, 58 ins. diam., bears N. 77° W., 35 lks.
dist., with scribe marks 4 S visible on
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.



Set a 6 ft. steel fence post alongside the iron post.

The 1/4 sec. cor. of secs. 7 and 18, determined from the
original bearing trees

A fir, 28 ins. diam., bears S. 49 1/2° E., 20 lks.
dist., with healed double blaze.