

County Surveyor's Record, Douglas County, Oregon

17727

Corrective Dependent Resurvey of the East One-Half Mile
of the Line Between Sections 20 and 29,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

29.15

Dirt road, 15 lks. wide, bears S. 20° E. and N. 15° W.

40.18

The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 23 S R 6 W
1/4 $\frac{S 20}{S 29}$
1957

form which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 22 ins. diam., bears N. 21° E.,
73 lks. dist., with healed blaze.

A fir, 35 ins. diam., bears S. 49° W.,
74 lks. dist., with healed blaze.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 23 S., R. 6 W.,
Willamette Meridian, Oregon

(Restoring the survey by William Thiel in 1879, the
resurvey and survey by John A. McQuinn in 1884, the
resurvey by Otis O. Gould, Joseph S. Gawron, and
Orville N. Eggen from 1943 to 1957, and the
corrective resurvey by Floyd A. Brooks in 1964)

From the cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 23 S R 6 W
S 26 | S 25
S 35 | S 36
1943

from which the remains of the original bearing trees

A fir root crown, size indeterminate, bears
S. 47 3/4° E., 52 lks. dist., no marks visible.

A sawed cedar stump, 50 ins. diam., bears
N. 43 3/4° W., 64 lks. dist., no marks visible.
(Record, N. 45 3/4° W.)

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A grand fir, 32 ins. diam., bears S. 16° E.,
85 lks. dist., with healed blaze.

A fir snag, 16 ins. diam., bears S. 66 1/2° W.,
27 lks. dist., with healed blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1972

A fir, 14 ins. diam., bears N. 11° E.,
32 lks. dist., with healed double blaze.

A fir, 24 ins. diam., bears S. 82° W.,
17 lks. dist., with healed double blaze.