

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, 17728  
 T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A maple, 15 ins. diam., bears N. 86 1/2° W., 31 lks. dist., with scribe marks R6W S26 CS visible on partially healed double blaze.

From this point, United States Geological Survey triangulation station "YELLOW 1904", bears N. 64° 19' W., 161.92 chs. dist., monumented with a standard brass tablet, 3 1/2 ins. diam., set in a boulder projecting 2 ins. above ground, mkd. X on top.

N. 10° 51' E., bet. secs. 25 and 26, marking and blazing the true line.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

11.90 Gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.

39.55 The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap melted, no marks, from which the remains of an original bearing tree:

A root hole, bears East, 77 lks. dist., with a down fir alongside, size indeterminate, no marks visible.

and remains of bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1962

A fir, 17 ins. diam., bears N. 11° E., 76 lks. dist., with healed double blaze.

A fir snag, 14 ins. diam., bears S. 41° W., 131 lks. dist., with scribe marks 1/4 S26 CS BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S    R 6 W  
           1/4  
           S 26 | S 25  
           1982

from which a new bearing tree

A fir, 4 ins. diam., bears S. 53 1/2° W., 13 1/2 lks. dist., mkd. X BT.

Deposit 1 in. diam. iron post alongside iron post.

N. 0° 48' W., beginning new measurement.

Descend over broken NW. slope.

19.28 The N 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

N 1/16  
           S 26 | S 25  
           1957