

County Surveyor's Record, Douglas County, Oregon

17729

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A grand fir, 16 ins. diam., bears S. 67 1/2° E.,
19 lks. dist., with healed blaze.

A root hole, bears S. 50 1/2° W., 30 lks. dist., with
down fir stump alongside, 10 ins. diam., with
scribe marks N 1/16 S26 BT visible on open blaze.

and a bearing tree mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962

A fir, 22 ins. diam., bears N. 7° W.,
63 lks. dist., with healed blaze.

N. 1° 00' W., beginning new measurement.

Descend over NW. slope.

2.45 Dirt road, 25 lks. wide, bears N. 25° E. and S. 25° W.

5.50 Creek, 2 lks. wide, course N. 70° W.; asc. over SW. slope.

8.40 Top of ascent, slopes W.; desc. over NW. slope.

17.85 Creek, 1 lk. wide, course S. 80° W.; asc. over SW. slope.

19.36 The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 23 S	R 6 W
S 23	S 24
S 26	S 25
57	
1943	

from which the remaining original bearing tree

A fir, 42 ins. diam., bears East, 80 lks. dist.,
with fragmentary scribe marks visible on
opened blaze. (Record, S. 90° E.)

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 15 ins. diam., bears N. 12° E.,
37 lks. dist., no marks visible. (Record,
33 lks.)

A sawed fir stump, 32 ins. diam., bears S. 66° E.,
5 lks. dist., with scribe marks R6W S25 visible
on open blaze.

A chinquapin, 19 ins. diam., bears S. 14° W.,
64 lks. dist., with healed blaze. (Record,
S. 12° W.)

A root hole, bears N. 15° W., 40 lks. dist.,
with a down fir alongside, 19 ins. diam.,
with healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. 77° E., 35
lks. dist., mkd. T23S R6W S24 BT.