

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17730**
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir, 9 ins. diam., bears S. 52° E., 65
lks. dist., mkd. T23S R6W S25 BT.

A fir, 5 ins. diam., bears N. 8° W., 10 1/2
lks. dist., mkd. X BT.

Land, mountainous.
Soil, rocky clay.
Timber, maple, oak, cedar, hemlock, yew, fir, pine,
madrone, alder, and chinquapin; undergrowth, poison oak,
arrowwood, hazel, huckleberry, blackberry, salal, fern,
Oregon grape, vine maple, salmonberry, thimbleberry,
ceanothus, wild rose, and young timber.

From the 1/4 sec. cor. of secs. 26 and 27, monumented with
an iron post, 2 ins. diam., firmly set, projecting 2 ins.
above ground, with brass cap mkd.

T 23 S R 6 W
 1/4
 S 27 | S 26
 1957

*Fd BE 8/90
M110-47*

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 22 ins. diam., bears S. 69° E., 97 lks.
dist., with healed blaze. (Record, S. 73° E.,
93 lks.)

A fir, 9 ins. diam., bears S. 86° W., 41 lks.
dist., with healed blaze.

N. 6° 59' W., bet. secs. 26 and 27.

Ascend along E. slope, through heavy timber and dense
undergrowth.

4.35 Spur, slopes E.; desc. over NE. slope.

12.20 Creek, 5 lks. wide, course E.; asc. over broken SW.
slope.

15.20 Spur, slopes S. 60° E.; desc. over NE. slope.

18.96 The N 1/16 sec. cor. of secs. 26 and 27, monumented with
an iron post, 2 ins. diam., firmly set, projecting 12
ins. above ground, with brass cap mkd.

N 1/16
S 27 | S 26
1957

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 27 ins. diam., bears N. 46° E., 10
lks. dist., with healed blaze.

A fir, 14 ins. diam., bears S. 66° W., 34
lks. dist., with healed blaze.

N. 7° 07' W., beginning new measurement.

Descend over NE. slope.

4.75 Creek, 5 lks. wide, course SE.; asc. over SW. slope.