

# County Surveyor's Record, Douglas County, Oregon

17731 Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

18.99

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 23 S	R 6 W
S 22	S 23
S 27	S 26
1943	

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 6 ins. diam., bears N. 25° E., 18 lks. dist., with healed blaze. (Record, N. 35° E.)

A fir, 8 ins. diam., bears S. 85 1/2° E., 38 lks. dist., with healed blaze.

A fir, 29 ins. diam., bears S. 29° W., 19 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 56° W., 10 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, oak, chinquapin, pine, cedar, fir, yew, alder, madrone, hemlock, maple, and ash; undergrowth, poison oak, hazel, Oregon grape, salal, arrowwood, salmonberry, blackberry, fern, vine maple, ceanothus, manzanita, wild rose, and young timber.

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 04' W., bet. secs. 23 and 26.

Descend over SW. slope, through heavy timber and dense undergrowth.

12.55

Creek, 2 lks. wide, course NW.; asc. over NE. slope.

17.95

Spur, slopes N. 30° W.; desc. over NW. slope.

20.42

The E 1/16 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

E 1/16	S 23
	S 26
1957	

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 15 ins. diam., bears N. 29° E., 9 lks. dist., with healed blaze.

A root hole, bears S. 26° E., 56 lks. dist., with down fir alongside, 12 ins. diam., with fragmentary scribe marks visible on open decayed blaze.

and a bearing tree of no record

A fir, 15 ins. diam., bears N. 86° W., 27 lks. dist., with healed blaze.

and a new bearing tree