

# County Surveyor's Record, Douglas County, Oregon

17733 Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

oak, Oregon grape, salal, arrowwood, salmonberry, blackberry, huckleberry, vine maple, ceanothus, manzanita, wild rose, fern, and young timber.

From the cor. of secs. 20, 21, 28, and 29.

N. 18° 36' E., bet. secs. 20 and 21.

Ascend over SE. slope, through heavy timber and dense undergrowth.

3.65 Dirt road, 20 lks. wide, bears S. 75° E. and N. 70° W.

3.90 Ridge, bears S. 75° E. and N. 65° W.; desc. over NE. slope, changing to NW. slope.

40.36 The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, with brass cap mkd.

T 23 S    R 6 W  
          1/4  
          S 20 | S 21  
          1957

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 21 ins. diam., bears N. 42° E., 51 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 50 1/2° W., 41 lks. dist., with healed blaze.

N. 19° 07' E., beginning new measurement.

Descend over NW. slope.

27.90 Head of ravine, drains W.; desc. over NW. slope.

36.80 Creek, 10 lks. wide, course N. 45° E.; asc. over SE. slope.

41.10 The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 23 S    R 6 W  
          S 17 | S 16  
          S 20 | S 21  
          1957

Fd 8/90  
M110-53

from which the remaining original bearing tree

A fir, 28 ins. diam., bears N. 20° W., 30 lks. dist., with scribe marks T23S R6W S17 BT visible on bark blaze.

and bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 32 ins. diam., bears N. 66 1/2° E., 17 lks. dist., with healed blaze.

A cedar, 24 ins. diam., bears S. 52° E., 36 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 24 1/4° W., 32 lks. dist., with scribe marks T23S R6W S17 BT visible on open blaze. (Record, N. 27° W.)