

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17736**
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

16.00

Creek, 3 lks. wide, course W.; asc. over S. slope, changing to SW. slope.

21.74

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 23 S	R 6 W
S 18	S 17
S 19	S 20
1957	

from which the remaining original bearing trees

A fir, 28 ins. diam., bears S. 42° W., 20 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 32 ins. diam., bears North, 21 lks. dist., with scribe marks R6 18 visible on bark blaze. (Record, 9 lks.)

and bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 28 ins. diam., bears N. 48 1/2° E., 46 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. 24 1/2° E., 205 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 36 1/2° W., 46 lks. dist., with healed blaze. (Record, S. 38 1/2° W.)

Land, mountainous.

Soil, sandy loam.

Timber, fir, hemlock, cedar, madrone, maple, and alder; undergrowth, poison oak, salal, arrowwood, vine maple, and young timber.

From the W 1/16 sec. cor. of secs. 17 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

W 1/16	S 17
	S 20
1957	

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 12 ins. diam., bears S. 24° W., 87 lks. dist., with healed blaze. (Record, 117 lks.)

A fir, 14 ins. diam., bears N. 5 3/4° W., 117 lks. dist., with healed blaze. (Record, N. 60° W., 89 lks.)

N. 88° 33' W., bet. secs. 17 and 20.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

14.20

Spur, slopes N. 40° W.; desc. over SW. slope.

17.61

The cor. of secs. 17, 18, 19, and 20.

Land, mountainous.

Soil, clay loam.