

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon 17738

CHAINS	
65.50	Ravine, drains S. 85° E.; asc. over SE. slope.
72.80	Spur, slopes S. 80° E.; desc. over NE. slope.
79.10	Ravine, drains E.; asc. over SE. slope.
81.25	Spur, slopes S. 80° E.; desc. over NE. slope.
83.55	Ravine, drains S. 85° E.; asc. over SW. slope.
83.89	The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. above ground, with brass cap mkd.
	T 23 S R 6 W 1/4 $\frac{S 17}{S 20}$ 1957
	from which bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 16 ins. diam., bears S. 56 1/2° E., 53 lks. dist., with healed blaze. (Record, 56 lks.)
	A cedar, 12 ins. diam., bears N. 32° W., 25 lks. dist., with healed blaze.
	From the 1/4 sec. cor. of secs. 20 and 21.
	N. 88° 52' W., on the E. and W. center line of sec. 20.
	Descend over NW. slope, through heavy timber and dense undergrowth.
6.75	Creek, 5 lks. wide, course N. 10° E.; asc. over E. slope.
12.80	Spur, slopes N. 20° E.; desc. over W. slope.
18.72	Point for the center E 1/16 sec. cor. of sec. 20.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	C $\frac{E 1/16}{S 20}$ C 1983
	from which
	A fir, 22 ins. diam., bears S. 26 1/4° E., 30 lks. dist., mkd. CE 1/16 S20 BT.
	A hemlock, 7 ins. diam., bears N. 26 1/2° W., 20 lks. dist., mkd. CE 1/16 S20 BT.
	Descend over NW. slope.
23.05	Creek, 5 lks. wide, course N. 30° E.; asc. over NE. slope.
27.70	Spur, slopes N. 55° E.; desc. over NW. slope.
33.65	Ravine, drains N. 40° E.; asc. over NE. slope.
37.44	The center 1/4 sec. cor. of sec. 20.
	Ascend over E. slope.