

County Surveyor's Record, Douglas County, Oregon

17739

Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
55.30	Ridge, bears N. and S.; desc. over SW. slope.
56.32	Point for the center W 1/16 sec. cor. of sec. 20. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> C $\frac{W \ 1/16}{S \ 20}$ C 1983 </div> from which A fir, 8 ins. diam., bears S. 75 1/2° E., 30 lks. dist., mkd. CW 1/16 S20 BT. A fir, 12 ins. diam., bears N. 45 1/2° W., 23 lks. dist., mkd. CW 1/16 S20 BT. Descend over SW. slope.
60.95	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
75.20	The 1/4 sec. cor. of secs. 19 and 20.
5.35	From the center E 1/16 sec. cor. of sec. 20. N. 20° 35' E., on the N. and S. center line of the NE 1/4 of sec. 20. Ascend over broken SW. slope, through heavy timber and dense undergrowth.
20.15	Spur, slopes N. 70° W.; desc. over NW. slope.
25.40	Creek, 10 lks. wide, course NE.; asc. over broken SE. slope.
28.85	Spur, slopes S. 85° E.; desc. NE. slope.
41.67	Ravine, drains S. 75° E.; asc. over SW. slope. The E 1/16 sec. cor. of secs. 17 and 20, monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. <div style="text-align: center;"> E 1/16 $\frac{17}{20}$ 1957 </div> from which bearing trees mkd. by Gould, Gawron, and Eggen A fir, 20 ins. diam., bears N. 16° E., 13 lks. dist., with healed blaze. A fir, 21 ins. diam., bears S. 48 1/2° E., 3 lks. dist., with healed blaze.
	From the E 1/16 sec. cor. of secs. 20 and 29. N. 20° 20' E., on the N. and S. center line of the SE 1/4 of sec. 20. Descend over NE. slope, through heavy timber and dense undergrowth.