

County Surveyor's Record, Douglas County, Oregon 137

Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

17740

CHAINS	
28.05	Creek, 5 lks. wide, course N.; asc. over SW. slope, changing to W. slope.
40.97	The center E 1/16 sec. cor. of sec. 20.
21.47	<p>From the center W 1/16 sec. cor. of sec. 20 .</p> <p>N. 23° 40' E., on the N. and S. center line of the NW 1/4 of sec. 20.</p> <p>Descend over NE. slope, through heavy timber and dense undergrowth.</p> <p>Point for the NW 1/16 sec. cor. of sec. 20 at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 20 1983</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 39 1/2° W., 18 lks. dist., mkd. NW 1/16 S20 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 3 1/2° W., 48 1/2 lks. dist., mkd. NW 1/16 S20 BT.</p> <p>Descend over NE. slope, changing to NW. slope.</p>
25.50	Gravelled road, 20 lks. wide, bears N. 45° E. and S. 60° W.
42.95	The W 1/16 sec. cor. of secs. 17 and 20.
18.20	<p>From the center N 1/16 sec. cor. of sec. 20.</p> <p>N. 88° 35' W., on the E. and W. center line of the NW 1/4 of sec. 20.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p> <p>The NW 1/16 sec. cor. of sec. 20.</p> <p>Ascend over NE. slope.</p>
19.95	Spur, slopes N. 20° E.; desc. over NW. slope.
23.40	Gravelled road, 20 lks. wide, bears N. 15° E. and S. 10° W.
36.42	The N 1/16 sec. cor. of secs. 19 and 20.
	<p>Subdivision of Section 26, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p>
	From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.