

County Surveyor's Record, Douglas County, Oregon

17741

Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

T 23 S R 6 W

1/4 $\frac{S\ 26}{S\ 35}$

1957

from which bearing trees mkd. by Gould, Gawron, and Eggen

A hemlock, 18 ins. diam., bears N. 39° E., 122 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, 120 lks.)

A fir, 9 ins. diam., bears S. 11° E., 58 lks. dist., with healed blaze.

N. 1° 00' W., on the N. and S. center line of sec. 26.

Descend over NE. slope, through heavy timber and dense undergrowth.

1.40 Creek, 1 lk. wide, course N. 70° W.; asc. over broken SW. slope.

9.15 Top of ascent, slopes SW.; desc. over broken NW. slope.

28.90 Dirt road, 25 lks. wide, bears N. 75° E. and S. 75° W.

38.23 Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 6 W

C 1/4

S 26

1982

from which

A fir, 8 ins. diam., bears N. 85° E., 12 1/2 lks. dist., mkd. C 1/4 S26 BT.

A fir, 18 ins. diam., bears S. 31 1/2° W., 34 lks. dist., mkd. C 1/4 S26 BT.

Descend 80 ft. over NW. slope.

42.60 Yellow Creek, 30 lks. wide, course S. 70° W.; asc. over SE. slope.

52.25 Spur, slopes E.; desc. over NE. slope.

57.29 The center N 1/16 sec. cor. of sec. 26, established by Wilford N. Haines, Registered Land Surveyor, No. 239, during an unrecorded survey, date unknown, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with a steel washer, 1 in. diam., mkd. WILFORD N HAINES DRAIN OREGON SURVEY POINT 239, and is accepted as the corner, from which bearing trees mkd. by Haines:

A fir, 27 ins. diam., bears S. 28 3/4° W., 17 lks. dist., with scribe marks CN 1/16 S26 BT. visible on bark blaze.

A fir, 19 ins. diam., bears N. 52 3/4° W., 34 lks. dist., with healed blaze.