

County Surveyor's Record, Douglas County, Oregon

17743

Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

59.15

The center W 1/16 sec. cor. of sec. 26, established by Wilford N. Haines, Registered Land Surveyor, No. 239, during an unrecorded survey, date unknown, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 6 ins. above ground, with a steel washer, 1 in. diam., mkd. WILFORD N HAINES DRAIN OREGON SURVEY POINT 239, and is accepted as the corner, from which bearing trees mkd. by Haines:

A fir, 16 ins. diam., bears N. 73° W., 18 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears N. 29° W., 11 lks. dist., with healed blaze .

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

C $\frac{W \ 1/16}{S \ 26}$ C
1982

from which a new bearing tree

A fir, 23 ins. diam., bears S. 60° W., 30 lks. dist., mkd. CW 1/16 S26 BT.

Reset iron rod alongside iron post.

S. 89° 43' W., beginning new measurement.

Descend over SW. slope.

2.05

Creek, 6 lks. wide, course S. 40° E.; asc. over NE. slope, changing to E. slope.

18.37

The 1/4 sec. cor. of secs. 26 and 27.

From the center E 1/16 sec. cor. of sec. 26.

N. 0° 56' W., on the N. and S. center line of the NE 1/4 of sec. 26.

Descend over broken NW. slope, through heavy timber and dense undergrowth.

19.17

The NE 1/16 sec. cor. of sec. 26, established by Wilford N. Haines, Registered Land Surveyor, No. 239, during an unrecorded survey, date unknown, monumented with a "T" shaped iron rod, 3/4 in. diam., firmly set, projecting 4 ins. above ground, with a steel washer, 1 in. diam., mkd. WILFORD N HAINES DRAIN OREGON SURVEY POINT 239, and is accepted as the corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

NE 1/16
S 26
1982

from which