

County Surveyor's Record, Douglas County, Oregon

17744

Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

	<p>A fir, 11 ins. diam., bears S. 40 1/2° E., 52 1/2 lks. dist., mkd. NE 1/16 S26 BT.</p> <p>A fir, 8 ins. diam., bears N. 20° W., 56 lks. dist., mkd. X BT.</p> <p>Reset iron rod alongside iron post.</p> <hr/> <p>N. 0° 56' W., beginning new measurement. Descend over NW. slope. Spur, slopes W.; desc. over broken NW. slope.</p>
<p>0.45 7.15 9.45 19.21</p>	<p>Creek, 2 lks. wide, course N. 75° W.; asc. over SW. slope. Spur, slopes W.; desc. over NW. slope. The E 1/16 sec. cor. of secs. 23 and 26.</p>
<p>1.15 20.44</p>	<p>From the N 1/16 sec. cor. of secs. 25 and 26. S. 89° 25' W., on the E. and W. center line of the NE 1/4 of sec. 26. Descend over broken SW. slope, through heavy timber and dense undergrowth. Dirt road, 25 lks. wide, bears N. 30° E. and S. 25° W. The NE 1/16 sec. cor. of sec. 26.</p>
<p>12.90 17.55 20.41</p>	<p>S. 89° 25' W., beginning new measurement. Descend over broken SW. slope, changing to NW. slope. Yellow Creek, 20 lks. wide, course S. 5° E.; asc. over broken SE. slope. Creek, 5 lks. wide, course S. 70° E.; asc. over NE. slope. The center N 1/16 sec. cor. of sec. 26.</p>
<p>18.97</p>	<p>From the center W 1/16 sec. cor. of sec. 26. N. 4° 04' W., on the N. and S. center line of the NW 1/4 of sec. 26. Ascend over SW. slope, through heavy timber and moderate undergrowth. Point for the NW 1/16 sec. cor. of sec. 26, at intersec- tion with the E. and W. center line of the NW 1/4. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 26 1982</p> <p>from which</p>