

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17748
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS' OFFICE

T 28 S

1/4	S 9	S 10
-----	--------	---------

R 7 W
1961

from which the remains of bearing trees mkd. by Bryon

A fir, 14 ins. diam., bears S. 68° E., 49 lks.
dist., with a healed blaze.

A fir stump, 17 ins. diam., bears N. 20° W.,
8 lks. dist., with a healed blaze.

and a new bearing tree

A fir, 17 ins. diam., bears S. 56 3/4° W., 23 lks.
dist., mkd. 1/4 S9 BT.

N. 0° 11' W., bet. secs. 9 and 10, marking and blazing
the true line.

Ascend SE. slope, through scattering timber and moderate
undergrowth.

2.60 Spur, slopes S. 75° E.; also dirt road, 15 lks. wide,
bears S. 75° E. and N. 70° W.; desc. N. slope.

10.30 Dirt road, 15 lks. wide, bears S. 80° E. and N. 80° W.

19.65 Point for the N 1/16 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

N 1/16		
S 9		S 10

1983

from which

A fir, 10 ins. diam., bears N. 54 1/2° E., 31 lks.
dist., mkd. N. 1/16 S10 BT.

A pine, 11 ins. diam., bears S. 63 1/4° W., 8 lks.
dist., mkd. N 1/16 S9 BT.

Descend over N. slope.

36.55 Creek, 10 lks. wide, course N. 65° E.; asc. SE. slope.

39.05 Larson Road, asphalt surface, 35 lks. wide, bears
N. 55° E. and S. 75° W.

39.30 The cor. of secs 3, 4, 9, and 10, reestablished at
proportionate dist. and recorded by G. G. Stewart, Deputy
Douglas County Surveyor, in 1922, monumented with an iron
pipe, 3/4 in. diam., firmly set flush with the ground,
and further perpetuated and recorded by James W. Byron.
Deputy Douglas County Surveyor, in 1961. There is no
remaining evidence of the original cor. This point is
accepted as the cor., from which a bearing tree mkd. by
Stewart

A black oak, 13 ins. diam., bears N. 10° W.,
38 lks. dist., with a healed blaze.