

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17750
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

- 11.35 Spur, slopes S. 15° W.; desc. over SW. slope.
- 15.30 Ravine, drains S. 15° W.; asc. over SE. slope.
- 19.95 Spur, slopes S.; desc. over SW. slope.
- 24.95 Ravine, drains S. 10° E.; asc. over SE. slope.
- 33.35 Ridge, bears N. 30° E. and S. 30° W.; desc. over NW. slope.
- 39.24 The cor. of secs. 8, 9, 16, and 17, determined at record bearing and dist. from the remaining original bearing tree

A madrone, 36 ins. diam., bears N. 57½° E.,
100 lks. dist., no marks visible on partially
opened blaze.

and the remains of bearing trees mkd. by Mensch

A fir, 8 ins. diam., bears N. 51° E.,
32 lks. dist., with a healed single blaze.

A sawed fir stump, 26 ins. diam., bears S. 42° E.,
24 lks. dist., with S16 visible on a cut open
blaze.

A fir, 28 ins. diam., bears S. 84° W.,
42 lks. dist., with a healed blaze.


A fir, 24 ins. diam., bears N. 39¼° W.,
31 lks. dist., with a healed blaze.

and bearing tree recorded by Jelley

A fir, 20 ins. diam., bears N. 74° E.,
37½ lks. dist., with a healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam.,
24 ins. in the ground, with aluminum cap mkd.



from which a new bearing tree

A fir, 6 ins. diam., bears S. 40½° E.,
241 lks. dist., mkd. T28S R7W S16 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, maple, oak, cedar, and alder;
undergrowth, salal, poison oak, and fern.

N. 0° 56' E., bet. secs. 8 and 9.

Descend over NE. slope, through heavy timber and dense
undergrowth.