

County Surveyor's Record, Douglas County, Oregon

17751

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7W., Willamette Meridian, Oregon

CHAINS

19.17

The S 1/16 sec. cor. of secs. 8 and 9, established and recorded by Virgil L. Broadwater, Oregon Registered Land Surveyor, No. 682, in 1972, and accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, from which bearing trees mkd. by Broadwater

A fir, 18 ins. diam., bears S. 37 1/2° E.,
86 lks. dist., with a healed blaze.

A cedar, 24 ins. diam., bears S. 45 1/2° W.,
118 lks. dist., scribe marks 1/16 S8 BT
visible on an open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, directly atop the 1 in. iron pipe,
with aluminum cap mkd.

S 1/16
S 8 | S 9
1983

from which a new bearing tree

A black oak, 8 ins. diam., bears S. 32° E.,
39 lks. dist., mkd. S 1/16 S9 BT.

N. 0° 55' E., beginning new measurement.

Descend over NE. slope

11.10 Creek, 10 lks. wide, course S. 58° E.; asc. SE. slope.

16.15 Larson Road, dirt surface, 15 lks. wide, bears N. 75° E.
and S. 75° W.

19.16 The 1/4 sec. cor. of secs. 8 and 9, reestablished by proportionate measurement by Claude Kerr, Registered Logging Engineer, No. 2125, in 1953, perpetuated by James W. Byron, Deputy Douglas County Surveyor, in 1961, and accepted as the cor., monumented with an iron pipe, 1 1/4 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S
1/4 S 8 | S 9
R 7 W
1961

from which bearing trees by Kerr

A cedar, 18 ins. diam., bears N. 74 3/4° E.,
19 lks. dist., with a healed double blaze.

A madrone 18 ins. diam., bears S. 76 1/2° W.,
42 lks. dist., with a healed double blaze

N. 0° 23' E., beginning new measurement.