

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

17752

**CHAINS**

Ascend SE. slope.

19.62

The N 1/16 sec. cor. of secs. 8 and 9, established and recorded by Virgil L. Broadwater, Registered Land Surveyor, No. 682, in 1972, and accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Broadwater

A fir, 14 ins. diam., bears N. 42 1/2° E.,  
27 lks. dist., with scribe marks 1/16 visible  
on an opened blaze.

A madrone, 16 ins. diam., bears S. 17 1/2° E.,  
24 lks. dist., with scribe marks 1/16 S9 BT  
visible on a partially healed blaze.

A fir, 16 ins. diam., bears N. 79 1/2° W.,  
45 lks. dist., with a healed blaze.

and a bearing tree of no known record.

A fir, 14 ins. diam., bears S. 4° E.,  
22 lks. dist., with a healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,  
22 ins. in the ground, directly atop the 1 in. iron pipe,  
with aluminum cap mkd.

N 1/16		
S 8		S 9
1983		

N. 0° 26' E., beginning new measurement.

Ascend SE. slope.

0.60

Ridge bears N. 60° E. and S. 50° W.; desc. NE. slope.

13.70

Creek, 12 lks. wide, course N. 64° E.; asc. S. slope.

19.45

Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.

19.67

The cor. of secs. 4, 5, 8, and 9, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1961, from a bearing tree mkd. by Mensch no longer in existence, and further perpetuated and recorded by Larry Monrean, Deputy Douglas County Surveyor, in 1976, monumented with an iron pipe, 1 1/4 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.

T 28 S    R 7 W

S 5		S 4
S 8		S 9

1976

from which the remains of the bearing trees mkd. by Byron