

County Surveyor's Record, Douglas County, Oregon

17753

Dependent Resurvey, Portion of Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A white oak, 6 ins. diam., bears N. 19° E.,
36 lks. dist., with a healed double blaze.

A white oak, 8 ins. diam., bears N. 41° E.,
41 lks. dist., with marks T28S R7W S4 CS visible
on an opened blaze.

A fir, 18 ins. diam., bears S. 51/2° E., 86 lks.
dist., with a healed double blaze.

and a bearing tree mkd. by Monrean

A cedar, 8 ins. diam., bears N. 65 1/2° W., 40 lks.
dist., with scribe marks T28S R7W S5 CS BT
visible on a partially healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 60 1/2° W., 62 lks.
dist., mkd. T28SR7W S8 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, yew, oak, maple, and
madrone; undergrowth, poison oak, Oregon grape, hazel,
salal, ferns, arrowwood, blackberry, and young timber.

From the cor. of secs. 3, 4, 9, and 10.

S. 89° 50' W., bet. secs. 4 and 9.

Ascend SE. slope, through scattering timber and moderate
undergrowth.

3.60 Spur, slopes S. 10° W.; desc. SW. slope, changing to
nearly level land.

12.40 Larson Road, asphalt surface, 35 lks. wide, bears
N. 85° W. and S. 80° E.; continue over level land.

19.82 The E 1/16 sec. cor. of secs. 4 and 9, established and
recorded by G. Robert Lecklider, Registered Professional
Engineer, No. 4079, in 1957, and accepted as the cor.,
determined from the remaining bearing tree mkd. by
Lecklider

A fir, 24 ins. diam., bears N. 18 1/2° E.,
245 lks. dist., with healed double blaze.

At the corner point

Set a steel spike, 8 ins. long, 1/4 in. diam., 8 ins. into
the asphalt surface of Larson Road, from which a new
bearing tree and a reference monument

A white oak, 8 ins. diam., bears S. 42 1/4° W.,
32 lks. dist., mkd. E 1/16 S9 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam.,
set 24 ins. in the ground, for a reference
monument, bears S. 67 1/4° W., 26 3/4 lks.
dist., with brass cap mkd. RM E 1/16 S9
17.6 FT 1983 and an arrow pointing to the
true corner point.

The cor. is located 2 lks. North of the S. edge of Larson
Road, 35 lks. wide, bears N. 89° E. and S. 89° W.