

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

17756

**CHAINS**

A fir, 14 ins. diam., bears S.  $48\frac{1}{2}^{\circ}$  E., 31 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.

A fir, 14 ins. diam., bears N.  $70^{\circ}$  W., 40 lks. dist., with a healed double blaze.

At the corner point

Set an aluminum post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 28 S    R 7 W  
           S 8  
 1/4                 
           S 17  
  
           1983

Deposit the iron pipe alongside the iron post.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, oak, madrone, maple, hemlock, alder, and ash; undergrowth, poison oak, salal, wild grass, vine maple, arrowwood, hazel, fern and young timber.

Subdivision of Section 9,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

From the  $1/4$  sec. cor. of secs. 9 and 16.

N. $0^{\circ}$  36' W., on the N. and S. center line of sec. 9.

Ascend SE. slope, through heavy timber and dense undergrowth.

11.05 Ridge, bears N.  $54^{\circ}$  E. and W.; desc. NE. slope.

19.15 Point for the center S  $1/16$  sec. cor. of sec. 9.

Set an aluminum post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

          C  
 S 1/16    |    S 9  
           C

1983

from which

A white fir, 8 ins. diam., bears N.  $10\frac{3}{4}^{\circ}$  E., 17 lks. dist., mkd. CS  $1/16$  S9 BT.

A fir, 12 ins. diam., bears S.  $76\frac{1}{2}^{\circ}$  W., 14 lks. dist., mkd. CS  $1/16$  S9 BT.

32.00 Creek, 3 lks. wide, course N.  $70^{\circ}$  W.; asc. SW. slope.

32.70 Spur, slopes S.  $50^{\circ}$  W.; desc. NW slope.

38.30 Point for the center  $1/4$  sec. cor. of sec. 9, at intersection with the E. and W. center line