

County Surveyor's Record, Douglas County, Oregon

17757

Subdivision of Section 9,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 28 S R 7 W

C 1/4

S 9

1983

from which

A cedar, 8 ins. diam., bears N. 8° E., 11 lks. dist., mkd. C 1/4 S9 BT.

A fir, 10 ins. diam., bears S. 12° E., 19 lks. dist., mkd. C 1/4 S9 BT.

Descend NW. slope.

55.30 Barbed wire fence, extends E. and W.

56.79 Point for the center N 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
 |
 N 1/16 S 9
 |
 C

1983

from which

A fir, 15 ins. diam., bears N. 56 1/4° E., 77 lks. dist., mkd. CN 1/16 S9 BT.

A white oak, 8 ins. diam., bears N. 83 1/2° W., 189 lks. dist., mkd. CN 1/16 S9 BT.

From this point a fence cor. bears S. 20 1/2° E., 156 lks. dist., with fences extending N., S., E., and W.

Descend nearly level land through pasture.

60.75 Creek, 10 lks. wide, course E., asc. SW. slope.

74.00 Larson Road, asphalt surface, 35 lks. wide, bears N. 86° E. and N. 84° W.

75.28 The 1/4 sec. cor. of secs. 4 and 9.

From the 1/4 sec. cor. of secs. 9 and 10.

N. 86° 41' W., on the E. and W. center line of sec. 9.

Ascend SE. slope, through heavy timber and dense undergrowth.

16.90 Ridge. bears N. 51° E. and S. 45° W., desc. NW. slope.

19.73 Point for the center E 1/16 sec. cor. of sec. 9, is located on a steep bluff, 35 ft. high, where it is impracticable to establish a permanent monument.