

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9,
T. 28 S., R. 7 W., Willamette Meridian, Oregon **17758**

CHAINS


From this point a cor. established by G. Robert Lecklider, Oregon Registered Engineer, No. 4079, in 1957, bears N.29° 57' W., 1.04 chs. dist., monumented with an iron pipe, 3/4 in. diam., projecting 10 ins. above the ground, from which bearing trees mkd. by Lecklider

A fir, 10 ins. diam., bears N. 85° E., 20 lks. dist., with a healed double blaze.

A fir, 24 ins. diam., bears S. 42° W., 33 lks. dist., with a healed double blaze.

19.87 Point selected for the witness cor. to the center E. 1/16 sec. cor. of sec. 9.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



1983

from which

A madrone, 10 ins. diam., bears N. 34° E., 49 lks. dist., mkd. X BT.

A fir, 12 ins. diam., bears S. 66 1/2° W., 19 lks. dist., mkd. X BT.

Descend over NW. slope.


39.46 The center 1/4 sec. cor. of sec. 9.

Descend over NW. slope.

58.50 Creek, 5 lks. wide, course N. 35° W.; asc. over NE. slope.

58.56 Point for the center W 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



FDOK BY Greg Lang
7-2000 M135-25

from which

A fir, 5 ins. diam., bears S. 27° E., 1ks. dist., mkd. X BT. 26.1 ft per lang

A fir, 8 ins. diam., bears N. 1/2° W., 41 lks. dist., mkd. CS 1/16 S9 BT.

Ascend over nearly level land.

59.10 Gravelled road, 15 lks. wide, bears S. 25° E. and N. 22° W.

59.50 Creek, 10 lks. wide, course N. 22° E.; asc. over nearly level land.

75.25 Larson Road, gravel surface, 15 lks. wide, bears N. 48° E. and S. 60° W.