

# County Surveyor's Record, Douglas County, Oregon

17759

Subdivision of Section 9,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS  
77.66

The 1/4 sec. cor. of secs. 8 and 9.

From the true point for the center E 1/16 sec. cor. of sec. 9.

N. 0° 20' W., on the N. and S. center line of the NE 1/4 of sec 9.

Descend over SW slope.

0.90 Rock bluff, 75 ft. high, edge bears N. 55° E. and S. 30° W.; desc. over N. slope.

19.07 Point for the NE 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16

S 9

1983

from which

A fir, 7 ins. diam., bears S. 68 1/4° E., 21 1/2 lks. dist., mkd. NE 1/16 S9 BT.

A fir, 10 ins. diam., bears N. 18 1/4° W., 16 1/2 lks. dist., mkd. NE 1/16 S9 BT.

From this point a fence cor. bears S. 45° W., 1.55 chs. dist., with fences extending N. 2° W. and N. 84° W.

Descend over N. slope.

37.15 Creek, 8 lks. wide, course N. 62° E.; asc. over nearly level land.

38.00 Barbed wire fence, extends E. and W.

38.12 The E 1/16 sec. cor. of secs. 4 and 9.

From the N 1/16 sec. cor. for secs. 9 and 10.

N. 88° 25' W., on the E. and W. center line of the NE 1/4 of sec. 9.

Descend over broken NW. slope changing to N. slope.

14.05 Dirt road, 15 lks. wide, bears S. 56° E. and N. 56° W.

19.77 The NE 1/16 sec. cor. of sec. 9.

Descend over broken N. slope, changing to nearly level land.

20.85 Barbed wire fence, extends N. and S.

39.00 Barbed wire fence, extends N. and S.

39.57 The center N 1/16 sec. cor. of sec. 9.

From the center S 1/16 sec. cor. of sec. 9.