

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 9,  
T. 28 S., R. 7 W., Willamette Meridian, Oregon

17760

CHAINS	
	N. 86° 42' W., on the E. and W. center line of the SW1/4 of sec. 9.
	Descend over broken NW. slope, changing to NE. slope.
38.73	The S 1/16 sec. cor. of secs 8 and 9.
<hr/>	
	From the center W 1/16 sec. cor. of sec. 9.
	N. 0° 05' W., on the N. and S. center line of the NW 1/4 of sec. 9.
	Along creek bottom.
0.05	Creek, 5 lks. wide, course N. 35° W.; asc. over nearly level land.
0.95	Creek, 15 lks. wide, course N. 45° E.; asc. over nearly level land.
11.80	Larson Road, asphalt surface, 35 lks. wide, bears N. 27° E. and S. 27° W.; also begin to asc. SE. slope.
19.07	Point for the NW 1/16 sec. cor. of sec. 9.
	Set an iron post. 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16
	S 9
	1983
	from which
	A fir, 10 ins. diam., bears N. 71 1/4° E., 9 lks. dist., mkd. NW 1/16 S9 BT.
	A fir, 8 ins. diam., bears S. 23 1/2° E., 52 lks. dist., mkd/ NW 1/16 S9 BT.
	Ascend over SE. slope.
29.10	Spur, slopes N. 80° E.; desc. over NE. slope.
38.14	The W 1/16 sec. cor. for secs. 4 and 9.
<hr/>	
	From the center N 1/16 sec. cor. for sec. 9.
	N. 84° 58' W.; on the E. and W. center line of the NW 1/4 of sec. 9.
	Descend over nearly level land.
7.95	Creek, 10 lks. wide, course N. 22° E.; asc. over SE. slope.
17.95	Larson Road, asphalt surface, 35 lks. wide, bears N. 36° E. and S. 36° W.
18.98	The NW 1/16 sec. cor. of sec. 9.
	Ascend over SE. slope.
37.95	The N 1/16 sec. cor. of secs. 8 and 9.