

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, 17764  
T. 25 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

T 25 S R 4 W  
1/4  
S 23 | S 24  
1957

from which the remains of the original bearing trees

A root hole, bears S. 12 1/4° E., 17 lks. dist., with fir stump alongside, no marks visible. (Record, S. 10° E., 14 lks.)

A cedar snag, 17 ins. diam., bears N. 45 3/4° W., 14 lks. dist., no marks visible on opened blaze. (Record, N. 50° W., 15 lks.)

and bearing trees marked by James Byron, County Surveyor in 1956.

A root hole, bears N. 44 1/2° E., 45 lks. dist., with downed cedar alongside, 25 ins. diam., with healed double blaze.

A cedar, 34 ins. diam., bears S. 49 1/2° W., 45 lks. dist., with healed double blaze.

and the remains of the bearing trees marked by Zirpel, Roseberry, and Corbin.

A cedar stump, 16 ins. diam., bears N. 73° E., 70 lks. dist., no marks visible. (Record, N. 68 3/4° E., 82 lks.)

A cedar, 16 ins. diam., bears S. 82 1/2° W., 80 lks. dist., with healed blaze. (Record, 84 lks.)

and a new bearing tree

A fir, 4 ins. diam., bears N. 68 1/2° E., 33 lks. dist., mkd. X BT.

N. 5° 10' E., bet. secs. 23 and 24, marking and blazing the true line.

18.65 Ravine, drains E.; asc. over SE. slope.

26.55 Spur, slopes N. 45° E.; desc. over NW. slope.

39.49 The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 25 S R 4 W  
S 14 | S 13  
S 23 | S 24  
1957

from which local bearing trees recorded by Zirpel, Roseberry, and Corbin

A dogwood, 9 ins. diam., bears N. 34 3/4° E., 7 lks. dist., no marks visible on partially healed double blaze.