

County Surveyor's Record, Douglas County, Oregon

17767

Dependent Resurvey, Portion of the Subdivisional Lines,
T 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir stump, 23 ins. diam., bears S. 61° E.,
46 lks. dist., with healed blaze.
(Record, S. 57 1/2° E., 45 lks.)

A cedar, 31 ins. diam., bears N. 14 1/4° W.,
30 1/2 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.
(Record, N. 12 3/4° W., 33 lks.)

and a bearing tree mkd. by Zirpel, Roseberry, and Corbin

A cedar, 10 ins. diam., bears S. 14° W., 40 lks.
dist., with healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 23° W., 41 lks.
dist., mkd. 1/4 S23 BT.

From this point, the Douglas County Surveyors Office
Horizontal Control Station, "HIGH 1971", bears
S. 2° 45' E., 17.99 chs. dist., monumented with a brass
disk, 2 1/2 ins. diam., set in concrete, mkd. Douglas County
Surveyors Office HIGH 1971.

S 88° 08' W., bet. secs. 23 and 26.

Descend over NW. slope, through scattering timber and
dense undergrowth.

2.25 Creek, 1 lk. wide, course N. 30° E.; asc. over E. slope.

11.75 Spur, slopes N.; desc. over W. slope.

17.25 Gravelled road, 15 lks. wide, bears N. 5° W., and S. 5° E.

19.36 The W 1/16 sec. cor. of secs. 23 and 26, perpetuated and
recorded by Vernon R. Tracy, Deputy County Surveyor, in
1969, monumented with an iron pipe, 1 1/2 ins. diam., firmly
set, projecting 8 ins. above the ground, with brass cap

COUNTY SURVEYORS OFFICE

T 25 S
W 1/16 S 23
 S 26
 R 4 W
 1969

FD OK
K HOFFINE
2/8/2007
CS65/60-25

from which the remains of a bearing tree mkd. by Zirpel
Roseberry, and Corbin

A fir snag, 36 ins. diam., bears N. 24 1/4° E.,
58 1/2 lks. dist., with scribe marks 1/16 S23 BT
visible on opened blaze.

and bearing trees mkd. by Tracy

A madrone, 10 ins. diam., bears N. 86° E.,
88 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

A madrone, 10 ins. diam., bears S. 45° W.,
53 1/2 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.