

County Surveyor's Record, Douglas County, Oregon

17773

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, hemlock, madrone, and maple;
undergrowth, arrowwood, poison oak, vine maple, salal,
and young timber.

N. 0° 01' W., bet. secs. 27 and 28.

Ascend over S. slope, through scattering timber and dense undergrowth.

3.90 Ridge, bears E. and W.; desc. over N. slope, changing to NW. slope.

15.75 Head of ravine, drains N. 80° W.; asc. over SW. slope.

20.05 The S 1/16 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

S 1/16
S 28 | S 27
1957

from which the remains of the bearing trees mkd. by Zirpel, Roseberry, and Corbin

A cedar, 32 ins. diam., bears N. 52° E.,
52 lks. dist., with healed blaze.

A cedar stump, 36 ins. diam., bears S. 64 1/2° W.,
37 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 79° W., 40 lks.
dist., mkd. S 1/16 S28 BT.

N. 0° 02' W., beginning new measurement.

Ascend over SW. slope.

6.10 Spur, slopes N.; desc. over NW. slope, changing to N. slope.

20.09 The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.

T 25 S R 4 W
1/4
S 28 | S 27
1957

from which a bearing tree mkd. by Zirpel, Roseberry, and Corbin

A fir, 13 ins. diam., bears S. 20° E., 98 lks.
dist., with healed blaze.

and a bearing tree mkd. by Vernon Tracy, Deputy County Surveyor, in 1965