

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17774**
 T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A yew, 18 ins. diam., bears S. 44° W., 48 lks. dist., with scribe marks 4 S28 CS BT visible on partially healed blaze.

N. 0° 04' W., beginning new measurement.

Descend over N. slope.


4.75 Creek, 3 lks. wide, course N. 20° W.; asc. over SW. slope, changing to broken W. slope.

20.08 Point for the N 1/16 sec. cor. of secs. 27 and 28, determined at record bearing and distance from the remaining bearing tree mkd. by Zirpel, Roseberry, and Corbin

A fir, 16 ins. diam., bears S. 68° W., 29 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



from which a new bearing tree

A fir, 9 ins. diam., bears N. 10 1/2° E., 39 lks. dist., mkd. N 1/16 S27 BT.

From this point, a point established and recorded by Vernon Tracy, Deputy County Surveyor, in 1965, bears South, 0.485 chs. dist., monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. WC T25S R4W 32 Ft N to N 1/16 S 27 S28 1965, from which the remains of the bearing trees mkd. by Tracy

A cedar stump, 32 ins. diam., bears S. 56° E., 31 lks. dist., with a healed double blaze.

A fir, 8 ins. diam., bears S. 87° W., 39 lks. dist., with a healed double blaze.

N. 0° 09' E., beginning new measurement.

Ascend over SW. slope.

2.50 Top of ascent, slopes W.; desc. over NW. slope, changing to N. slope.

15.75 Creek, 5 lks. wide course W.; asc. over S. slope.

17.60 Dirt road, 15 lks. wide, bears N. 85° W., and S. 80° E.

20.05 The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.