

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17776**  
 T. 25 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

38.12

The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 25 S R 4 W  
 1/4      $\frac{S\ 22}{S\ 27}$   
 1957

from which the remains of bearing trees mkd. by F. J. Cole, Deputy County Surveyor, in 1914

A fir snag, 30 ins. diam. bears S. 15 1/4° E.,  
 32 1/2 lks. dist., no marks visible on opened blaze.

A fir stump, 20 ins. diam., bears N. 22 1/2° W.,  
 7 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and the remains of the bearing trees mkd. by Zirpel, Roseberry, and Corbin

A cedar, 17 ins. diam., bears N. 53 3/4° E.,  
 47 1/2 lks. dist., with healed blaze.

A fir snag, 17 ins. diam., bears S. 24 1/4° W.,  
 87 lks. dist., with healed blaze.

and a new bearing tree

A cedar, 11 ins. diam., bears S. 1 3/4° W.,  
 53 1/2 lks. dist., mkd. 1/4 S27 BT.

Corner is located at fence corner, with fence lines extending N., S., E., and W.

N. 89° 30' W., beginning new measurement.

Descend over W. slope, changing to SW. slope.

9.60

Foot of descent, slopes SW.; asc. over SE. slope.

10.30

Dirt road, 15 lks. wide, bears N. 45° E. and S. 45° W.

15.05

Spur, slopes S. 20° E.; desc. over broken SW. slope.

20.14

The W 1/16 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

W 1/16      $\frac{S\ 22}{S\ 27}$   
 1957

from which the remains of a bearing tree mkd. by Zirpel, Roseberry, and Corbin

A cedar snag, 12 ins. diam., bears S. 6° W.,  
 27 lks. dist., no marks visible.

and bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1965